



Spartan Chemical Company, Inc.

Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):
SSE CARPET PRESpray & SPOTTER
 Product Number: 3033; 3035

Product Division:
Janitorial

Spartan Chemical Company, Inc.
 1110 Spartan Drive
 Maumee OH 43537

Product/Technical Information: **1-(800)-537-8990**
 Medical Emergency: **1-(888)-314-6171 (24 hours)**
 Chemical Leak/Spill Emergency: **CHEMTREC 1-(800) 424-9300 (24 hours)**

Shipping Description: Cleaning compounds, liquid, n.o.s.

NFPA Ratings:	HMIS Ratings:
Health: 1- Slight Fire: 0 - Minimal Reactivity: 0 - Minimal	Health: 1- Slight Fire: 0 - Minimal Reactivity: 0 - Minimal Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

Chemical Name(s)	%Wt	CAS Registry No.	Table Z-1-A			NTP, IARC or OSHA Carcinogen
			TWA mg/m ³	STEL mg/m ³	CEILING mg/m ³	
Acrylic copolymer	1-5	63744-68-3	Not Established	Not Established	Not Established	No
Propylene glycol monomethyl ether	1-5	107-98-2	369 (ACGIH)	553 (ACGIH)	Not Established	No

SECTION III: PHYSICAL DATA

Boiling Point: 212 °F	Vapor Pressure: Not determined
Vapor Density (AIR = 1): Unknown	Solubility in Water: Complete
pH: 8.5 -9.5	Specific Gravity (H ₂ O=1): 1.01
Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight: 1-5
Physical State: Liquid	
Appearance & Odor: Light green liquid, citrus fragrance	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 212°F	Method Used: ASTM-D56
Flammable Limits: Not Established	Flame Extension: N/A
Extinguishing Media: Product does not support combustion. Use extinguishing media appropriate for surrounding fire.	
Special Fire Fighting Procedures: Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed containers with water spray.	
Unusual Fire & Explosive Hazards: Combustion products are toxic.	

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value: Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes and Oral
Effects of Overexposure- Conditions to Avoid:	May cause eye and skin irritation. Symptoms may include pain, redness and swelling. May be harmful if swallowed. Symptoms may include abdominal pain and diarrhea. Inhalation of product vapors or mist may cause respiratory irritation. Avoid contact with eyes and skin . Do not swallow. Avoid breathing product vapors or mist . Wash thoroughly after handling .
Conditions Aggravated by Use:	Use of this product may aggravate preexisting skin; eye and respiratory disorders including asthma and dermatitis.
Emergency & First Aid Procedures :	
Eyes:	Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses. Get medical attention.
Skin:	Wash skin thoroughly with soap and water. Get medical attention if irritation persists. Wash contaminated clothing before reuse.
Ingestion:	Do not induce vomiting. Drink one or two glasses of water to dilute product. Get medical attention. Do not give anything by mouth to an unconscious person.
Inhalation:	In case of respiratory irritation; move person to fresh air. Get medical attention if irritation persists.

SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials: Strong oxidizers
Hazardous Decomposition Products: CO, CO2	Hazardous Polymerization: Will Not Occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:	Small spills of one gallon or less may be flushed with plenty of water to sanitary sewer system (If permitted by local sewer regulations). Dike and contain large spills with inert material and transfer liquid to containers for disposal. Keep spill out of storm sewers and waterways.
Waste Disposal Method:	Dispose of in compliance with all federal, state and local laws and regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection:	None required
Ventilation:	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Rubber or other impervious gloves are recommended.
Eye Protection(Specify Type):	Splash goggles are recommended.
Other Protective Equipment:	See 29 CFR 1910.132-138 for further guidance.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing:	Keep from freezing.
Other Precautions:	Keep out of reach of children.

© SCC 08/22/2008	Name: Ronald T. Cook	Title: Manager, Regulatory Affairs
SSE CARPET PRESPRAY & SPOTTER	Effective Date: 08/22/2008	Supercedes: 07/07/2005
Ref: 29 CFR 1910.1200 (OSHA)	Changes: Review	

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.